LGR Mobile Dehumidifier - SM1501

Features

- * Upto 150 Liter Per Day @ Saturation.
- * Powerful 1600m3/h airflow.
- * Superior all temperature performance
- * Sensor controlled thermodynamic defrose cycle
- * Graphical user interface touch pad control panel with Humidity & Timer Control
- * Loss Power Protection with Auto Restart.



Application & functioning

Mode of functioning

Condensation principle (heat-pump technology with energy recovery)

Area of use

Closed rooms (water damage, building drying, ect.)

Suitable for

Room size upto 800m³ - (at building drying or water damage elimination)

Room size upto 1500m3 - (at keep drying)

Dimensions & installation

Mobility

Mobile

Initiation

Put plug into power socket. Turn on the unit and set the required humidity.

Condensate Pump

Automatic pump out.

Condensate outlet

Condensate-hose can be fast connnected.

Air flow

Air inlet at the front, air outlet at the back.

Dimensions (W x D x H)

550 X 495 X 920mm

Weight

75Kg

Included Accessories

HAF filter

Water drain hose, 10 meters

Technical Data

Casing

Hot - dip galvanized sheet steel, coated with inside and outside, easy to dismantle.

Dehumidifiying performance / Watt

150L/per day @ 32 ° C, 90%RH / 2100W

Air Circulation rate

1600m3/h

Operation range

Temperture: 1° C - 38° C

Adjust Humidity Range: 25% RH up to 80% RH

Protection Grade

IPX0

Noise level

56dB(A)

Voltage

220V-240V/50Hz

Max. Ampere

9A

Meter

Kwh meter

Control

Touch pad control panel with Humidistat &Timer

Air Filter

HAF filter

<u>Cable</u>

8meters with plug

Compressor Type / Refrigent

Rotary / 410A CFC free

<u>Guarantee</u>

12 months from purchase



Suntec Industries (H.K.) Ltd.

Tel: +852 81300676 Fax: +852 81300671