

LGR Mobile Dehumidifier SD801

- with Humidity & Timer Control

Features

- * Upto 85 Liter Per Day @ saturation.
- * Powerful 750m³/h airflow.
- * Superior all-temperature performance
- * Performance optimized @ 32° C 90%RH
- * Sensor controlled thermodynamic defrost cycle
- * Graphical user interface touch pad control panel with Humidity & Timer Control
- * Loss Power Protection with Auto Restart



Application & functioning

Mode of functioning

Condensation principle (heat-pump technology with energy recovery)

Area of use

Closed rooms (Flood & Fire restoration, museums, art galleries, storing, archives, ect.)

Dimensions & installation

Installation/mobility

Mobile

Initiation

Put plug into power socket. Turn on the unit and set the required humidity or Timer.

Condensate Pump

Automatic pump out.

Condensate outlet

Water drain hose can be fast connected.

Air flow

Air inlet at the front, air outlet from the back

Dimensions (W x D x H)

550 X 450 X 915mm

Weight

45Kg

Included Accessories

HAF filter

Water drain hose, 10 meters

Optional Accessories

Ducting Kit

Technical Data

Casing

Impact-resistant plastic (PE ployethylene)

Protection Class

IP 21

Dehumidifying performance/Watt

85L/per days @ 32° C 90%RH/ 1250W

54L/per days @ AHAM

Air Circulation rate

750m³/h

Operation range

Temperture: 1° C - 38° C

Adjust Humidity Range: 25% RH up to 80% RH

Noise Level

63 dB(A)

Defrost Type

Hot Gas Defrose

Power Supplier

220V-240V/50Hz

Ampere

5.5A

Control

Touch pad control panel with humidistat & Timer.

Air Filter

HAF filter

Cable

8 meters with plug

Compressor Type / Refrigerent

Rotary / R410A CFC free

Guarantee

12 months from purchase



Suntec Industries (H.K.) Ltd.

URL: www.suntecind.com Email:sales@suntecind.com