# **Swimming Pool Dehumidifier - SP1000/1000C**

## **Features**

- SP1000C comes with specially coated coils to guard against corrosion from condensation and from salt/chlorinated water
- ◆ Processor Controlled automatic hot-gas defrost system, allows effective operation down to 1°C
- ◆ Loss Power Protection with Auto Restart.
- Pressure protection system switches unit off (and later back on again) when the ambient temperature becomes too low or too high

## **Application & Functioning**

#### **Mode of functioning**

Condensation principle (heat-pump technology with energy recovery)

#### **Area Handling**

Indoor-pools with water surface upto approximate 80m² (60~80m²) \*\*\* Heated rooms upto 1100CBM; Unheated rooms upto 900CBM.

#### Suitable for

Indoor pools, sauna rooms, museums, art galleries, storage areas, archives, labs, greenhouses, etc.

# **Dimensions & Installation**

#### Installation/Mobility

Wall mount / Floor mount / Mobile

## Initiation

Put the plug into power socket. Turn on the unit and set the required humidity level

#### **Condensate Outlet**

Drain hose can be fast connected.

#### **Air Flow**

Air inlet at the front, air outlet from the top

# Dimensions (L x W x H)

890 X 260 X 750mm

# <u>Weight</u>

53 KG

## **Included Accessories**

Remote Control (1)

Bottom Wall Mounted Brackets & Plates(2) with Screws(8)

Floor Mounted Brackets (4)

Universal Wheels (4)

Water Drain Hose (1)

Condensation Hose Connector (1)

Template Plate (1)

External Automatic Condensation Pump (Optional)

# **Optional Accessories**

External Automatic Condensation Pump (1)

\*\* Depending on water and room temperature

Specifications are subject to change without notice. Some values are approximate.



# **Technical Data**

#### **Casing**

Hard Plastic, Splash & Rust resistant.

#### **Protection Class**

IP 22

#### **Dehumidifying Performance**

100L/per day @ 30°C / 80%RH

#### **Power Consumption / Ampere**

1500 Watt / 6.5 Amps

#### **Air Circulation Rate**

800m<sup>3</sup>/h

#### Operation Range

Temperature: 1 °C - 40 °C

Humidity Range: 10% RH up to 90% RH

#### **Noise Level**

48 dB(A)

#### **Defrost Type**

Hot Gas Defrost

# Power Supplier

220V-240V/50Hz

# Touchpad Control Panel

With Timer & Humidistat Control

Remote Control

#### Air Filter

Nylon Filter

#### Water Feed

**Gravity Feed** 

# <u>Cable</u>

3 meters with plug

# Compressor Type / Refrigerant

Rotary/ 410A CFC free

#### **Guarantee**

12 months from purchase



# Suntec Industries (H.K.) Ltd.